



Technical Features	FL-3000	FL-3300	FL-3500	FL-3800	FL-4200
A Maximum lifting height (from crackpin center)	3,20 m	3,50 m	3,75 m	4,00 m	4,50 m
B Maximum lifting height (from bottom of attachment)	2,95 m	3,30 m	3,50 m	3,80 m	4,25 m
C Loader boom center	1,5 m	1,75 m	1,90 m	2,15 m	2,45 m
D Loader bearing center	1,5 m	1,55 m	1,65 m	1,70 m	1,88 m
E Attachment dump angle	53 °	58 °	57 °	55 °	55 °
F Attachment rollback angle at max. lifting height	45 °	55 °	55 °	57 °	57 °
G Attachment rollback angle at bottom	41 °	45 °	45 °	44 °	44 °
H Digging depth	0,1 m	0,1 m	0,1 m	0,1 m	0,15 m
Time for lifting to max. height	5 Seconds	5 Seconds	5 Seconds	6 Seconds	7 Seconds
Lifting capacity	1.100KG	1.300KG	1.550KG	1.900KG	2.350KG
Weight of loader (w/o attachment)	500KG	530KG	600KG	640KG	800KG
Attachment balancing system	Standard	Standard	Standard	Standard	Standard
Soft drive	Standard	Standard	Standard	Standard	Standard
Joystick control system	Standard	Standard	Standard	Standard	Standard
Electro-hydraulic third line	Standard	Standard	Standard	Standard	Standard
Easy attachment change adaptor	Standard	Standard	Standard	Standard	Standard
Engine power of tractor that loader will be attached to	50-70HP	60-80HP	70-100HP	85-130HP	150-200HP
Max. weight of tractor that loader will be attached to	3.000KG	4.000KG	4.500KG	5.200KG	8.000KG