


UX-DOWNLIGHT 202 POLISHED

2x18W,TC-D, MB B2,9003

Order code: DA6401321832000



Gross weight	1.70 kg
LOR	39 %
LLPW	27.80 lm/w
Pallette quantity	150 pc

Lighting fixtures Downlights are suitable especially for mounting into different kinds of ceiling boards. The Downlights are best suited to office, classroom, sales areas, showrooms, presentation of merchandise, public buildings, banks, museums, hotels, exhibition halls, entrance areas, decorative entrance areas, foyers, corridors, staircases, conference rooms, etc.

CONSTRUCTION

Housing: galvanized sheet

Reflectors: aluminium with various types of surface

finish – polished, mat

Reflector cover: sandblasted hardened glass

Ring: sheet steel, electrostatic powder coat finish RAL

9003 (signal white), other finish types – RAL 9006 (white

aluminium), chrome or brass available on request

Ballast box: galvanized sheet steel, holders to prevent

conductors from loosening off the terminal box, two rubber

reducing adapters for conductors (through mounting

possible)

Ceiling attachment of the luminaire is done using two

metal springs, adjustable for various ceiling widths. The

cover glass is attached to the luminaire using three springs

allowing fast and tool-free light source replacement.

ELECTRICAL COMPONENTS

Luminaires can be equipped with conventional control

gear (EEI=B2, standardly not compensated), electronic

(EEI=A2) or dimmable electronic control gears (EEI=A1,

1-10V, switch DIM, DALI)

Light sources shall be ordered separately.

ACCESSORIES

- an independent metal box for separate placement of the ballast apart from the luminaire (separate gear box version):

- on request, they can be delivered with one or two connectors allowing fast electrical connection: 3-pole connectors Wieland gesis GST 18i3, Wago Winsta 770, AAG Stucchi 1601A/1602A

	OPTIC		POWER	LAMP	DIMENSIONS					OPENING		EMERGENCY		
	POLISHED	MAT			D1	D2	L1	L1/SB	H1	H2	A1	O1	1H	3H
UX-Downlight 202	*	*	1x13	TC-D,TC-DEL	195	155	305	212	110	54	152	175	*	*
UX-Downlight 202	*	*	1x18	TC-D,TC-DEL	195	155	305	212	110	54	152	175	*	*
UX-Downlight 202	*	*	1x26	TC-D,TC-DEL	195	155	305	212	110	54	152	175	*	*
UX-Downlight 202	*	*	2x13	TC-D,TC-DEL	195	155	305	212	110	54	152	175	*	*
UX-Downlight 202	*	*	2x18	TC-D,TC-DEL	195	155	305	212	110	54	152	175	*	*
UX-Downlight 202	*	*	2x26	TC-D,TC-DEL	195	155	305	212	110	54	15	175	*	*
UX-Downlight 212	*	*	1x18	TC-D,TC-DEL	230	196	359	250	126	70	172	205	*	*
UX-Downlight 212	*	*	1x26	TC-D,TC-DEL	230	196	359	250	126	70	172	205	*	*
UX-Downlight 212	*	*	2x18	TC-D,TC-DEL	230	196	359	250	126	70	172	205	*	*
UX-Downlight 212	*	*	2x26	TC-D,TC-DEL	230	196	359	250	126	70	172	205	*	*
UX-Downlight 222	*	*	1x18	TC-D,TC-DEL	267	228	378	269	143	87	172	240	*	*
UX-Downlight 222	*	*	1x26	TC-D,TC-DEL	267	228	378	269	143	87	172	240	*	*
UX-Downlight 222	*	*	1x32	TC-TEL	267	228	378	269	143	87	172	240	*	*
UX-Downlight 222	*	*	1x42	TC-TEL	267	228	378	269	143	87	172	240	*	*
UX-Downlight 222	*	*	2x18	TC-D,TC-DEL	267	228	378	269	143	87	172	240	*	*
UX-Downlight 222	*	*	2x26	TC-D,TC-DEL	267	228	378	269	143	87	172	240	*	*
UX-Downlight 222	*	*	2x32	TC-TEL	267	228	378	269	143	87	172	240	*	*

